

# Simplicity




Figure 1.

## Mfr's. No. 416

### PACKING

The Lift Lever is shipped in one carton. The contents of the carton are:

- 1 - Lift Lever Assembly
- 1 - Lift Lever Quadrant
- 1 - Lift Bar (Use On No. 442 Mower Only)
- 1 - Lift Chain
- 1 - Bag of Hardware

### ASSEMBLY INSTRUCTIONS

1. Attach the L.H. Bearing Bar to the Frame using the (2) 3/8-16 x 1" lg. capscrews and 3/8" lockwashers and hex nuts. Insert the Bar of the Lift Lever Assembly through the L.H. Bearing Bar. Attach the R.H. Bearing Bar which is assembled on the Lift Lever to the Frame. Secure with (2) 3/8-16 x 1" lg. capscrews and 3/8" lockwashers and hex nuts.

#### NOTE

The Top Mounting Hole On The R.H. Bearing Bar Is Also Used For Mounting The Lift Lever Quadrant.

2. Attach the lift lever quadrant using the above mentioned hardware and (1) 3/8-16 x 3/4" lg. espscrew and 3/8" lockwasher and 3/8" hex nut. Then attach the mower lift lever and chain assembly to the lift lever assembly.

### ON NO. 442 - 28" ROTARY MOWER

Attach the lift bar to the mower housing with (2) 3/8-16 x 3/4" capscrews, (2) 3/8" lockwasher and (2) 3/8"-16 hex nuts as shown and attach lower end of chain to bar as shown in figure 1.

### ON NO. 422 - 32" ROTARY MOWER

Remove hardware holding upper end of chain and reposition in end link. Fasten lower end of chain directly to the right hand stud on the mower cover with 3/8" plain washer, 3/8" lockwasher and 3/8"-16 hex nut as shown in figure 2.

## LIFT LEVER KIT





Figure 2.

PRINT IN U.S.A.



Ref. Let.	Part No.	Description
A	162069	R.H. Bearing Bar
B	162070	L.H. Bearing Bar
C	162068	Lift Lever Quadrant
D	705005	Hex Cap Screw 3/8"-16 x 1"
E	720002	Lock Washer 3/8"
F	717003	Hex Nut, Full 3/8"-16
G	705004	Hex Cap Screw 3/8"-16 x 3/4"
H	162066	Lift Lever Assembly
J	723011	Roll Pin 3/16" diam. x 1"
K	156222	Lift Lever Latch
L	723007	Roll Pin 3/8" diam. x 1"
M	156158	Lift Lever Latch Rod
N	722001	Cutter Pin 3/32" diam. x 3/4" lg.
P	154226	Spacer
Q	152006	Spring
R	154227	Thumb Button
S	156209	Handle Grip

Ref. Let.	Part No.	Description
T	153058	Pin
U	8161045	Spring Clip
V	108385	Mower Lift Lever
W	705031	Hex Cap Screw 3/8"-16 x 7/8"
X	717510	Hex Nut, Full Lock, 3/8"-16
Y	108375	Lift Bar (Use On No. 442 Mower Only)
Z	717003	Hex Nut, Full 3/8"-16
AA	720002	Lock Washer 3/8"
AB	108199	Mower Lift Link
AC	705005	Hex Cap Screw 3/8"-16 x 1"
AD	717510	Hex Nut, Full Lock, 3/8"-16
AE	107081	Chain
AF	705005	Hex Cap Screw 3/8"-16 x 1"
AG	719001	Plain Washer 3/8"
AH	720002	Lock Washer 3/8"
AK	717003	Hex Nut, Full 3/8"-16
AL	153058	Lock Pin